

# LED STANDARD WALL PACK



## FEATURES & BENEFITS

- Modular design allows for easy installation, replacement and maintenance. This design also creates a chimney effect which provides exceptional thermal management.
- Corrosion resistant polyester powder painted 100µ m thickness.
- Meets a 1000-hour salt spray certification per ASTM B117/ ISO 9227:2012.
- Over 20 optical lenses are available for virtually any application.
- High quality LEDs, driver and components, e.g. MOLEX, WAGO connectors.
- Multiple lighting control options are available, e.g. DALI, 1-10V
- 5 years limited warranty.
- Nichia 3535 LED Chips / Philips Advance Xitanium LED Driver.


\*IDA Approved if color temperature is 3000K or less\*

## CERTIFICATIONS

UL/ CUL/ LM79/ SAA/ ENEC/ CB/ CE/ ErP/ RoHS/ IK08

## TECHNICAL PARAMETERS

|                       |  |
|-----------------------|--|
| Power                 | 20-160W                                    |
| Input                 | 120-277VAC or 220-240VAC or 347-480VAC     |
| PF                    | >0.95                                      |
| THD                   | <20%                                       |
| L85                   | >60,000H                                   |
| Operating Temperature | -40°C ~ +50°C                              |
| Efficacy              | 125 - 135 lm/W                             |
| ANSI CCT              | 3000K/4000K/5000K/5700K                    |
| Min CRI               | 70 or 80 or 85                             |
| IP Rating             | IP65                                       |
| SPD                   | Optional                                   |
| DALI                  | Optional                                   |
| 1-10V                 | Optional                                   |
| Photocell             | /  |
| Smart Control         | /  |
| Optic (IESNA)         | Type I, Type II, Type III, Type IV, Type V |
| Color Options         | Grey/Black/Bronze/White                    |



## ORDERING INFORMATION

Example : APSWP-80-A1-50K-T4M-BK

| Fixture                    | Power (Watts) (40W/module)   | Voltage         | Color Temperature (CCT)  | Light Distribution (Lens Type)   | Fixture Color  | Mounting Options (Brackets) | Lighting Controls   | Accessory Info   |
|----------------------------|--|-----------------|--|--|--|-----------------------------|---|--|
| APSWP - Standard Wall Pack | 20 - 2,600 lumens<br>30 - 3,900 lumens<br>40 - 5,200 lumens<br>60 - 7,800 lumens<br>80 - 10,400 lumens<br>90 - 11,700 lumens<br>120 - 15,600 lumens<br>160 - 20,800 lumens | A1: 120-277V AC | 30K - 3000K  | T1M1 - Type I Medium   | GR - Grey<br>BK - Black<br>BZ - Bronze<br>WH - White<br>CU - Custom* | W - Wall Mount              | 00<br>Not required  | BLS - Back Light Shield**  |
|                            |  | B4: 347-480V AC | 40K - 4000K<br>50K - 5000K<br>57K - 5700K<br>AM - Turtle<br>Safe Amber | T2M1 - Type II Medium<br>T3M1 - Type III Medium<br>T3L1 - Type III Long<br>T4S1 - Type IV Short<br>T4M1 - Type IV Medium<br>T5U - 10°<br>T5V - 25°<br>T5W - 40°<br>T5S - 60°<br>T5M - 90°<br>T5L - 120°<br>T5X - 150°<br>T5D - Type V Diffuser |  |                             | 01<br>Photocell<br>02<br>Motion Sensor<br>03<br>Photocell +<br>Motion Sensor<br>04<br>DALI<br>05<br>1 - 10V dimming | RO - Rotated Optics**<br>Bird Spike<br>20KA Surge<br>Protection Device<br>Safety Cable<br>EM - Emergency<br>Backup |

\*Extra cost for custom color

\*\*Note this after lens type.